

Ground Station

For Power




Code No.	No. of Hole	Ø Stud (mm)	Busbar (mm)	Dimensions (mm)			Weight (kg)
				W	L	H	
GBPGSS-6	6	14.3	50 x 350 x 6	148	350	70	1.20
GBPGSS-8	8	14.3	50 x 440 x 6	148	440	70	1.20
GBPGSS-12	12	14.3	50 x 610 x 6	148	610	70	1.80
GBPGSS-6D	12	14.3	100 x 350 x 6	148	350	70	1.80
GBPGSS-8D	16	14.3	100 x 440 x 6	148	440	70	2.50
GBPGSS-12D	24	14.3	100 x 610 x 6	148	610	70	3.60

Tested : IEC 62561 - 1

Application : Connect ground conductor wires to earth electrode

Material : Tin Plated Copper Bar – BS EN 13601
Support – Hot Dip Galvanized Steel with Insulator Bolt -Stainless Steel

For Communication



Code No.	No. of Hole	Ø Stud (mm)	Busbar (mm)	Dimensions (mm)			Weight (kg)
				W	L	H	
GBCGSS-200	6	10	100 x 200 x 6	148	200	70	0.86
GBCGSS-300	11	10	100 x 300 x 6	148	300	70	1.60
GBCGSS-400	15	10	100 x 400 x 6	148	400	70	1.80
GBCGSS-450	18	10	100 x 450 x 6	148	450	70	2.40
GBCGSS-600	24	10	100 x 600 x 6	148	600	70	3.20

Tested : IEC 62561 - 1

Application : Connect ground conductor wires to earth electrode

Material : Tin Plated Copper Bar – BS EN 13601
Support – Hot Dip Galvanized Steel with Insulator Bolt -Stainless Steel

