ESP 240DS-32A



Products 4 Low Voltage Products and Systems 5 Surge Protective Devices 5 IEC/EN standard 5 Furse ESP Mains power protection

General Information

 Extended Product Type:
 ESP 240DS-32A

 Product ID:
 7TCA085460R0318

 EAN:
 5415022286892

Catalog Description: ESP 240DS-32A Surge Protective Device

Long Description: ESP 240DS-32A IN-LINE POWER SPD WITH ENHANCED LED STATUS INDICATION FOR 2

40V SUPPLIES UP TO 32A, WITH VOLT FREE CONTACT

Ordering

Ordering	
EAN:	5415022286892
Minimum Order Quantity:	1 piece
Customs Tariff Number:	8536908085
Dimensions	
Product Net Width:	36 mm
Product Net Height:	90 mm
Product Net Depth:	75 mm
Product Net Weight:	0.23 kg
r roddot rot Weight.	0.23 Ng
Container Information	
Package Level 1 Units:	1 piece
Package Level 1 EAN:	5415022286892
Environmental	
Ambient Air Temperature:	Operation -40 +80 °C
Anoen An Temperature.	Operation -40 +60 C
Additional Information	
Arrester Class:	I
Commontion Types	III
Connection Type:	Screw clamp
Discharge Current:	Nominal 20 kA I (max, 8 / 20 μs) 40 kA
Maximum Continuous Operating Voltage (U _c):	280 V
Nominal AC Voltage of the System (U _o):	240 V
Product Main Type:	Power SPD
Product Name:	Surge Protective Devices
Rated Frequency (f):	50 / 60 Hz
Short Circuit Withstand Icc:	350 V
Standards:	IEC 61643-11
Suitable For:	To protect systems against transient overvoltages or surges from lightning and electrical switching events
Temporary Overvoltage Test Value (U _T):	350 V
Voltage Protection Level (Up):	600 V
Wire Stripping Length:	9.5 mm
Certificates and Declarations (Docum	ent Number)
Data Sheet, Technical Information:	9AKK10103A0350
Declaration of Conformity - CE:	9AKK106713A0835
Instructions and Manuals:	9AKK106713A1362
Classifications	
ЕПМ 4:	EC000942 - Surge protection device for terminal equipment
ЕПМ 5:	EC000942 - Surge protection device for terminal equipment
ЕТІМ 6:	EC000942 - Surge protection device for terminal equipment

