

# ESP 30E



Products → Low Voltage Products and Systems → Surge Protective Devices → IEC/EN standard → Furse ESP data & signal protection

Products → Low Voltage Products and Systems → Surge Protective Devices → IEC/EN standard → Furse special products

## General Information

<b>Extended Product Type:</b>	ESP 30E
<b>Product ID:</b>	7TCA085400R0104
<b>EAN:</b>	5414363086345
<b>Catalog Description:</b>	ESP 30E Surge Protective Device
<b>Long Description:</b>	ESP 30E 30V DATA SPD FOR 2 WIRE LINES UP TO 1.25A CURRENT

## Ordering

<b>EAN:</b>	5414363086345
-------------	---------------

<b>Minimum Order Quantity:</b>	1 piece
--------------------------------	---------

<b>Customs Tariff Number:</b>	8536301000
-------------------------------	------------

## Dimensions

<b>Product Net Width:</b>	120 mm
---------------------------	--------

<b>Product Net Height:</b>	54 mm
----------------------------	-------

<b>Product Net Depth:</b>	19 mm
---------------------------	-------

<b>Product Net Weight:</b>	0.080 kg
----------------------------	----------

## Container Information

<b>Package Level 1 Units:</b>	1 piece
-------------------------------	---------

<b>Package Level 1 EAN:</b>	5414363086345
-----------------------------	---------------

## Environmental

<b>Ambient Air Temperature:</b>	Operation -40 ... +80 °C
---------------------------------	--------------------------

## Additional Information

<b>Connection Type:</b>	Screw clamp
-------------------------	-------------

<b>Discharge Current:</b>	I (max, 8 / 20 µs) 10 kA
---------------------------	--------------------------

<b>Maximum Continuous Operating Voltage (U<sub>c</sub>):</b>	36.7 V
--	--------

<b>Nominal AC Voltage of the System (U<sub>o</sub>):</b>	30 V
--	------

<b>Number of Protected Poles:</b>	1
-----------------------------------	---

<b>Product Main Type:</b>	Data SPD
---------------------------	----------

<b>Product Name:</b>	Surge Protective Devices
----------------------	--------------------------

<b>Rated Current (I<sub>n</sub>):</b>	1.25 A
---------------------------------------	--------

<b>Rated Frequency (f):</b>	45 MHz
-----------------------------	--------

<b>Standards:</b>	IEC 61643-21
-------------------	--------------

<b>Suitable For:</b>	To protect systems against transient overvoltages or surges from lightning and electrical switching events
----------------------	--

<b>Voltage Protection Level ( U<sub>p</sub>):</b>	43.5 V
---	--------

<b>Wire Stripping Length:</b>	6 mm
-------------------------------	------

## Certificates and Declarations (Document Number)

<b>Data Sheet, Technical Information:</b>	9AKK10103A0049
---	----------------

<b>Declaration of Conformity - CE:</b>	9AKK106713A0815
--	-----------------

<b>Instructions and Manuals:</b>	9AKK106713A1363
----------------------------------	-----------------

## Classifications

<b>ETIM 4:</b>	EC000943 - Surge protection device for data networks/MCR-technology
----------------	---

<b>ETIM 5:</b>	EC000943 - Surge protection device for data networks/MCR-technology
----------------	---

<b>ETIM 6:</b>	EC000943 - Surge protection device for data networks/MCR-technology
----------------	---

