ESP 415/I/TT



Products -> Low Voltage Products and Systems -> Surge Protective Devices -> IEC/EN standard -> Furse ESP Mains power protection

General Information

Extended Product Type: ESP 415/I/TT

Product ID: 7TCA085460R0102 **EAN**: 5414363472827

Catalog Description: ESP 415/I/TT Surge Protective Device

Long Description: ESP 415/III/TT TYPE 1+2 POWER SPD FOR SINGLE PHASE 415V TT S

UPPLIES, 25KA 10/350

Ordering

EAN: 5414363472827

Minimum Order Quantity: 1 piece

Customs Tariff Number: 8536303090

Dimensions

Product Net Width: 90 mm

Product Net Height: 90 mm

Product Net Depth: 68 mm

Product Net Weight: 1.0 kg

Container Information

Package Level 1 Units: 1 piece

Package Level 1 EAN: 5414363472827

Environmental

Ambient Air Temperature: Operation -40 ... +80 °C

Additional Information

Arrester Class:

Ш

Connection Type: Screw clamp

Discharge Current: Nominal 25 kA

Maximum 100 kA

Maximum Continuous Operating

Voltage (U_c):

320 V

Nominal AC Voltage of the System

(U_o):

230 V

Number of Protected Poles:

4

Product Main Type:	Power SPD
Product Name:	Surge Protective Devices
Rated Frequency (f):	50 / 60 Hz
Short Circuit Withstand Icc:	25 kA
Standards:	IEC 61643-11
Suitable For:	To protect systems against transient overvoltages or surges from lightning and electrical switching events
Temporary Overvoltage Test Value (U_T):	350 V
Type of Low Voltage Distribution System:	TT
Voltage Protection Level (Up):	1.4 kV
Wire Stripping Length:	11 mm

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	9AKK10103A0349
Declaration of Conformity - CE:	9AKK106713A1211
Instructions and Manuals:	9AKK106713A1357

Classifications

ETIM 4:	EC000941 - Surge protection device for power supply systems
ETIM 5:	EC000941 - Surge protection device for power supply systems
ETIM 6:	EC000941 - Surge protection device for power supply systems

