

ESP SL30L/4-20



Products → Low Voltage Products and Systems → Surge Protective Devices → IEC/EN standard
→ Furse ESP data & signal protection

General Information

Extended Product Type:	ESP SL30L/4-20
Product ID:	7TCA085400R0070
EAN:	5415022024296
Catalog Description:	ESP SL30L/4-20 Surge Protective Device
Long Description:	ESP SL30L/4-20 SLIM LINE DATA SPD WITH STATUS LED INDICATION FOR 4-20mA SYSTEMS

Ordering

EAN:	5415022024296
Minimum Order Quantity:	1 piece
Customs Tariff Number:	8536308000

Dimensions

Product Net Width:	106.5 mm
Product Net Height:	104.6 mm
Product Net Depth / Length:	7 mm
Product Net Weight:	0.08 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 EAN:	5415022024296

Environmental

Ambient Air Temperature:	Operation -40 ... +80 °C
---------------------------------	--------------------------

Additional Information

Connection Type:	Screw clamp
Discharge Current:	I (max, 8 / 20 μ s) 10 kA
Maximum Continuous Operating Voltage (U_c):	36.7 V
Nominal AC Voltage of the System (U_o):	30 V
Number of Protected Poles:	3
Product Main Type:	Data SPD
Product Name:	Surge Protective Devices

Rated Current (I_n):	75 mA
Rated Frequency (f):	45 MHz
Standards:	IEC 61643-21
Suitable For:	To protect systems against transient overvoltages or surges from lightning and electrical switching events
Voltage Protection Level (U_p):	45.4 V
Wire Stripping Length:	9.5 mm

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	9AKK10103A0054
Declaration of Conformity - CE:	9AKK106713A1076
Instructions and Manuals:	9AKK106713A1365

Classifications

ETIM 4:	EC000943 - Surge protection device for data networks/MCR-technology
ETIM 5:	EC000943 - Surge protection device for data networks/MCR-technology
ETIM 6:	EC000943 - Surge protection device for data networks/MCR-technology

