ESP SL30L/4-20/M



Products + Low Voltage Products and Systems + Surge Protective Devices + IEC/EN standard + Furse ESP protector accessories

General Information	
Extended Product Type:	ESP SL30L/4-20/M
Product ID:	7TCA085400R0164
EAN:	5415022110708
Catalog Description:	ESP SL30L/4-20/M Surge Protective Device
Long Description:	ESP SL30L/4-20/M SLIM LINE DATA SPD MODULE FOR ESP SL30L/4-20 DATA SPD RANGE
Ordering	
EAN:	5415022110708
Minimum Order Quantity:	1 piece
Customs Tariff Number:	8536301090
Dimensions	
Product Net Width:	106.5 mm
Product Net Height:	104.6 mm
Product Net Depth / Length:	7 mm
Product Net Weight:	0.08 kg
Container Information	
Package Level 1 Units:	1 piece
Package Level 1 EAN:	5415022110708
Environmental	
Ambient Air Temperature:	Operation -40 +80 °C
Additional Information	
Connection Type:	Screw clamp
Discharge Current:	I (max, 8 / 20 μs) 10 kA
Maximum Continuous Operating Voltage (U _c):	36.7 V
Nominal AC Voltage of the System (U _o):	30 V
Number of Protected Poles:	3
Product Main Type:	Data SPD
Product Name:	Surge Protective Devices

Rated Current (I _n):	75 mA
Rated Frequency (f):	45 MHz
Standards:	IEC 61643-21
Suitable For:	To protect systems against transient overvoltages or surges from lightning and electrical switching events
Voltage Protection Level (Up):	45.4 V
Wire Stripping Length:	9.5 mm
Certificates and Declarations (D	ocument Number)
Data Sheet, Technical Information:	9AKK10103A0365
Declaration of Conformity - CE:	9AKK106713A1265
Instructions and Manuals:	9AKK106713A1365

Classifications

ETIM 4:	EC000943 - Surge protection device for data networks/MCR-technology
ETIM 5:	EC000943 - Surge protection device for data networks/MCR-technology
ETIM 6:	EC002496 - Accessories for surge protection power supply systems

