



บริษัท เซฟโก้ จำกัด
SEFCO SUPPLY CO., LTD.
 321/35, 321/36 หมู่ 6 ต.สุรัสจันทน์ อ.สุรัสจันทน์ จ.ชลบุรี 20110
 321/35, 321/36 Moo. 6 Surasak Sriracha Chonburi 20110
 Email: sefco@sefco.co.th www.sefco.co.th
 Tel: (038) 119780-2 Fax: (038) 119783

SMOKECHECK

Home Safeguard Model 25 S (25 oz)



- UL/ULC Listed
Alarm Manufacturer Approved
- Meets all NFPA 72 and International
Fire Code Requirements
- Safe on Sensors
- Leaves No Residue
- Does Not Contribute to Global Warming
- Ozone Safe, Environmentally Friendly
- Meets Kyoto and Montreal Protocols



The Original — Accept No Imitations

Tested, Approved, and Preferred

Don't just take our word for it. Simply note that the highly regarded Underwriters Labs approved Smoke Detector Tester after subjecting the product to a series of rigorous torture tests. This independent lab not only approve Home Safeguard products but also use Home Safeguard's Smoke Detector Tester themselves to test smoke detectors submitted to them for approval. A number of smoke detector manufacturers also use the product in their manufacturing process, but that's not all. We are also the preferred choice of many government agencies, including all U.S. Veterans Administration hospitals (and many private hospitals, as well), Convalescent centers, U.S. Consumer Product Safety Commission, U.S. Embassies and military installations at home and abroad and municipal fire departments who also recommend the product to owners and managers of multiple-family dwellings and Fortune 500 companies are among our regular customers.



Institutional Size, Model 25S.

This exciting product designed specifically for supervised systems will tell you quickly, easily, and economically whether your smoke detectors are working or not. UL listed, this product is approved for testing smoke detectors function per NFPA 72 par. 8-2.4.1 when used as directed. TO USE: From a distance of 2 to 4 ft. (6-1.2m) aim spray for 1-2 seconds at the vents or side of the detector. Alarm will sound within 1 to 10 seconds if the detector functions properly unless the detector has a built-in delay circuit. Detectors with delay circuits should be sprayed 1 or 2 additional times to activate the alarm.

ใช้ตรวจสอบได้ถึง 200 ครั้งในกระป๋องเดียวโดยไม่ทำให้อุปกรณ์เสียหาย