

Kumwell

Blunt End Air Terminals

Copper



Code No.	Rod Length (L) (mm)	Rod Diameter (φ) (mm)	Thread (in)	Weight (kg)
LTAT 58-30	300	15	5/8	0.50
LTAT 58-50	500	15	5/8	0.80
LTAT 58-60	600	15	5/8	0.96
LTAT 58-100	1000	15	5/8	1.60
LTAT 58-150	1500	15	5/8	2.40
LTAT 58-200	2000	15	5/8	3.20
LTAT 34-30	300	19	3/4	0.75
LTAT 34-50	500	19	3/4	1.20
LTAT 34-60	600	19	3/4	1.51
LTAT 34-100	1000	19	3/4	2.50
LTAT 34-150	1500	19	3/4	3.80
LTAT 34-200	2000	19	3/4	5.00

Tested : IEC 62561 - 2

Application : Suitable for typical installation

Material : Copper – BS EN 13601

Aluminium



Code No.	Rod Length (L) (mm)	Rod Diameter (φ) (mm)	Thread (in)	Weight (kg)
LTAT 58-30A	300	16	5/8	0.16
LTAT 58-50A	500	16	5/8	0.27
LTAT 58-60A	600	16	5/8	0.33
LTAT 58-100A	1000	16	5/8	0.55
LTAT 58-150A	1500	16	5/8	0.82
LTAT 58-200A	2000	16	5/8	1.10

Tested : IEC 62561 - 2

Application : Suitable for installation on metal roof

Material : Aluminium – BS 2898