

Cable Support - LCAS



Code No.	Cable Size (mm ²)	Material	Weight (kg)
LCAS 25-35	25-35	Copper Alloy	0.060
LCAS 50-70	50-70	Copper Alloy	0.060
LCAS 95-120	95-120	Copper Alloy	0.080
LCAS 450-185	150-185	Copper Alloy	0.110
LCAS 240-300	240-300	Copper Alloy	0.170
LCAS 25-35 A	25-35	Aluminium Alloy	0.020
LCAS 50-70 A	50-70	Aluminium Alloy	0.020

Tested : IEC 62561-4

Application : Fix copper stranded or solid conductors

Material : Copper Alloy– BS EN 1982, Bolt – Brass

Aluminium Alloy – BS 2898, Bolt - Stainless Steel

Cable to Tape - LCTT



Code No.	Cable Size (mm ²)	Tape Size (mm)	Material	Weight (kg)
LCTT 70-253	35-70	25 x 3	Copper Alloy	0.264
LCTT 120-253	95-120	25 x 3	Copper Alloy	0.266
LCTT 70-254	35-70	25 x 4	Copper Alloy	0.276
LCTT 120-254	95-120	25 x 4	Copper Alloy	0.292
LCTT 70-256	35-70	25 x 6	Copper Alloy	0.303
LCTT 120-256	95-120	25 x 6	Copper Alloy	0.319

Tested : IEC 62561-1

Application : Connect copper tape conductors with copper

Stranded or solid conductors

Material : Copper Alloy– BS EN 1982, Bolt – Brass