

OVR T2 3L 40-275 P QS

General Information

Extended Product Type:	OVR T2 3L 40-275 P QS
Product ID:	2CTB803873R2400
EAN:	3660308519825
Catalog Description:	OVR T2 3L 40-275 P QS Surge Protective Device
Long Description:	B751982

Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » Surge Protective Devices SPDs » Surge Protective Devices SPD Class II

Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363090

Popular Downloads

Data Sheet, Technical Information:	2CTC432232D0201
Mechanical Drawings:	2CTC800021F0700.pdf 2CTC800021F0701.dxf 2CTC800021F0702.stp 2CTC800021F0703.igs

Dimensions

Product Net Width:	53.4 mm
Product Net Depth:	58 mm
Product Net Height:	88 mm
Product Net Weight:	360 g
Width in Number of Modular Spacings:	3

Technical

Type of Low Voltage Distribution System:	TN-C
Nominal AC Voltage of the System (U _o):	230 / 400 V
Number of Protected Poles:	3
Arrester Class:	II
Product Main Type:	T2
Standards:	IEC 61643-11 / EN 61643-11
Product Type:	QS
Version:	Plug-in
Discharge Current:	Nominal 20 kA Maximum 40 kA Total 120 kA
Impulse Current:	I (imp, 10 / 350 μs) 2 kA
Maximum Continuous Operating Voltage (U _c):	(L-PE) 275 V (L-L) 440 V (L-N) - V (N-PE) - V
Voltage Rating DC:	350 V
Voltage Protection Level (U _p):	(L-N) - kV (N-PE) - kV (L-PE) 1.25 kV
Short Circuit Withstand I _{cc} :	100 kA
Temporary Overvoltage Test Value (U _T):	337 V
Short-Circuit Protective Devices:	Curve B Breakers ≤ 125 A Curve C Breakers ≤ 125 A gL Type Fuses ≤ 125 A gG Type Fuses ≤ 125 A
Auxiliary Circuit Load:	Minimum - Maximum -
Power Loss:	28 mW
Product Name:	Surge Protective Device

Suitable For: To protect the systems against the transient overvoltage (lightning)

Certificates and Declarations (Document Number)

CB Certificate: [2CTC432024G1701](#)

Declaration: [2CTC432056G1701](#)

Declaration of Conformity - CE: [2CTC436004G1701](#)

Instructions and Manuals: [2CTC432096M1701](#)

Container Information

Package Level 1 Units: 1 piece

Package Level 1 Width: 117 mm

Package Level 1 Length: 61 mm

Package Level 1 Height: 82 mm

Package Level 1 Gross Weight: 375 g

Package Level 1 EAN: 3660308519825

Classifications

ETIM 4: EC000941 - Surge protection device for power supply systems

ETIM 5: EC000941 - Surge protection device for power supply systems

ETIM 6: EC000941 - Surge protection device for power supply systems

