

ESP 240DS-32A



Products → Low Voltage Products and Systems → Surge Protective Devices → IEC/EN standard → Furse ESP Mains power protection

General Information

Extended Product Type:	ESP 240DS-32A
Product ID:	7TCA085460R0318
EAN:	5415022286892
Catalog Description:	ESP 240DS-32A Surge Protective Device
Long Description:	ESP 240DS-32A IN-LINE POWER SPD WITH ENHANCED LED STATUS INDICATION FOR 2 40V SUPPLIES UP TO 32A, WITH VOLT FREE CONTACT

Ordering

EAN:	5415022286892
Minimum Order Quantity:	1 piece
Customs Tariff Number:	8536908085

Dimensions

Product Net Width:	36 mm
Product Net Height:	90 mm
Product Net Depth:	75 mm
Product Net Weight:	0.23 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 EAN:	5415022286892

Environmental

Ambient Air Temperature:	Operation -40 ... +80 °C
---------------------------------	--------------------------

Additional Information

Arrester Class:	I II III
Connection Type:	Screw clamp
Discharge Current:	Nominal 20 kA I (max, 8 / 20 µs) 40 kA
Maximum Continuous Operating Voltage (U_c):	280 V
Nominal AC Voltage of the System (U₀):	240 V
Product Main Type:	Power SPD
Product Name:	Surge Protective Devices
Rated Frequency (f):	50 / 60 Hz
Short Circuit Withstand I_{cc}:	350 V
Standards:	IEC 61643-11
Suitable For:	To protect systems against transient overvoltages or surges from lightning and electrical switching events
Temporary Overvoltage Test Value (U_T):	350 V
Voltage Protection Level (U_p):	600 V
Wire Stripping Length:	9.5 mm

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	9AKK10103A0350
Declaration of Conformity - CE:	9AKK106713A0835
Instructions and Manuals:	9AKK106713A1362

Classifications

ETIM 4:	EC000942 - Surge protection device for terminal equipment
ETIM 5:	EC000942 - Surge protection device for terminal equipment
ETIM 6:	EC000942 - Surge protection device for terminal equipment

